



WWW.SENDO.WORLD

55.000BTU



ARTEMIS

BRONZE COSTS, GOLD PERFORMANCE



R 32



INVERTER

ARTEMIS

floor standing cabinets

R 32  INVERTER 



Model		SFSU - 55 ART3	
-------	--	----------------	--

Power supply		Ph - V - Hz	380 - 415V, 3Ph, 50Hz
Rated cooling	Capacity	Btu / h	51000 (18000 ~ 57000)
Rated cooling	Capacity	kW	15,10 (6,50 ~ 15,50)
Cooling power input		W	5350 (1300 ~ 6000)
Cooling current		A	9 (2,5 ~ 10)
EER		W / W	2,82 / A
Rated heating	Capacity	Btu / h	60000 (15000 ~ 66000)
Rated heating	Capacity	kW	15,20 (5 ~ 16,20)
Heating power input		W	4500 (1000 ~ 5800)
Heating current		A	8 (2 ~ 9,5)
COP		W / W	3,38 / A
Seasonal cooling	Pdesignc	kW	14,1
	SEER	W / W	6,1
	Seasonal space cooling energy eff. ($\eta_{s,c}$)	%	241
Heating (average)	Pdesignh	kW	11,1
	SCOP	W / W	4,0
	Seasonal space heating energy eff. ($\eta_{s,h}$)	%	157
	Tbiv	°C	-7
Tol		°C	-15
Moisture removal		L / h	5,3
Max input consumption		W	9000
Max. current		A	14
Compressor	Type		ROTARY
	Brand		GMCC
	Capacity	Btu / h	46744
	Input	W	3700
	Rated current (RLA)	A	7,02
	Thermal protector position		External
	Refrigerant oil / oil charge	ml	VG74 / 1400
Outdoor fan motor	Output	W	210
	Speed (Hi / Mi / Lo)	r / min	540 / 500 / 460
Indoor air flow (Hi / Mi / Lo)		m ³ / h	2497 / 2380 / 2100
Indoor sound pressure level (Hi)		dB (A)	66

The company reserves the right to change the technical characteristics without notice.