



WWW.SEND0.WORLD

12.000 - 60.000 BTU



# CASSETTE UNITS

FEEL THE AIR ALL AROUND YOU



R 32



INVERTER



Wi-Fi Ready

# Cassette type air conditioning units multi split



Model			SFM - 09CU - AU1	SFM - 12CU - AU1	SFM - 18CU - AU1
Capacity	Cooling	Btu / h	9560 (5120-12115)	12285 (5800-12625)	17060 (8530-19107)
		kW	2,80 (1,50-3,55)	3,60(1,70-3,70)	5,0 (2,50-5,6)
	Heating	Btu / h	10240 (5460-13000)	13306 (6930-15080)	19107 (10340-24000)
		kW	3,00 (1,60-3,81)	3,9 (2,03-4,42)	5,6 (3,03-7,03)
Electric data	Power supply	V~,Hz,Ph	220~240, 50, 1	220~240, 50, 1	220~240, 50, 1
	Cooling power input	W	70 (17,5-109)	70 (17,5-109)	70 (17,5-109)
	Heating power input	W	70 (17,5-109)	70 (17,5-109)	70 (17,5-109)
Fan	Model		XD30B	XD30B	XD30B
	Brand		XINJUN	XINJUN	XINJUN
	Output power	W	30	30	30
	Capacitor		2	2	2
	Speed (Hi / Mi / Lo)	r / min	810 / 750 / 660	810 / 750 / 660	810 / 750 / 660
Indoor Coil	Number Of Row		2	2	2
	Tube x Row Pitch	mm	20,5 x 12,7	20,5 x 12,7	20,5 x 12,7
	Fin Pitch	mm	1,5	1,4	1,5
	Fin Material		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Tube Dia.& Material	mm	φ7, Inner grooved	φ7, Inner grooved	φ7, Inner grooved
	Coil L x H x W	mm	1320 x 205 x 25,4	1320 x 205 x 25,4	1320 x 205 x 25,4
	Heat Exchange Area	m <sup>2</sup>	6,12	6,12	6,12
Performance	Air flow volume	CFM	412 / 353 / 312	412 / 353 / 312	412 / 353 / 312
		m <sup>3</sup> / h	700 / 600 / 530	700 / 600 / 530	700 / 600 / 530
	Sound pressure noise level	dB (A)	45 / 41 / 35	45 / 41 / 35	45 / 41 / 35
	Sound power noise level	dB (A)	56	56	56
	ESP	Pa	570 x 570 x 260	570 x 570 x 260	570 x 570 x 260
Dimension	Net dimension (W * D * H)	mm	720 x 650 x 290	720 x 650 x 290	720 x 650 x 290
	Packing dimension (W * D * H)	mm	650 x 650 x 55	650 x 650 x 55	650 x 650 x 55
Weight	Net	kg	710 x 710 x 80	710 x 710 x 80	710 x 710 x 80
	Gross	kg	14,5	14,5	16
Refrigerant			17	17	18,5
Pipe diameter	Liquid side	mm (inch)	2,2	2,2	2,2
	Gas side	mm (inch)	3,7	3,7	3,7
	Drainage	mm	R32	R32	R32
Loading Qty	20/40/40H	unit	147 / 309 / 348	147 / 309 / 348	147 / 309 / 348

The company reserves the right to change the technical characteristics without notice.