



WWW.SENDO.WORLD



# HERMES GOLD

NOTHING ELSE MATTERS BUT SUPREMACY



R 32



INVERTER



Wi-Fi



PLASMA



GOLDEN FIN

# HERMES

wall-mounted air conditioning



R 32



INVERTER



Wi-Fi



GOLDEN FIN



EXTRA FILTERS



Model	Indoor Unit	SND - 09 HRS3-ID	SND - 12 HRS 3-ID	SND - 18 HRS 3-ID	SND - 24 HRS 3-ID
	Outdoor Unit	SND - 09 HRS3-OD	SND - 12 HRS3-OD	SND - 18 HRS3-OD	SND - 24 HRS3-OD

Nameplate parameter	Rated capacity		Cooling	W	2650 (620 - 3100)	3550 (800 - 4100)	5300 (1300 - 5700)	7300 (1800 - 7400)	
			Heating	W	2700 (820 - 3400)	3800 (1000 - 4200)	5300 (1300 - 5500)	7300 (1800 - 8000)	
	Rated power consumption		Cooling	W	810 (120 - 1600)	1180 (120 - 1600)	1650 (290 - 2100)	2200 (230 - 2760)	
			Heating	W	720 (320 - 1600)	1100 (300 - 1600)	1470 (250 - 1800)	2200 (230 - 2530)	
	Rated running current		Cooling	A	3,9 (0,9 - 6,9)	5,6 (0,7 - 7,8)	7,8 (2,2 - 9,3)	10,0 (1,0 - 12)	
			Heating	A	4,1 (1,5 - 8,0)	4,9 (1,5 - 8,0)	6,5 (2,0 - 8,0)	9,5 (1,0 - 11)	
	Max. input power				W	1600	1900	2500	3400
	Max. input current				A	9,5	9,5	12	16
	SEER cooling				W / W	6,50 / A+++	6,19 / A+++	6,50 / A+++	6,53 / A+++
	SCOP heating				W / W	4,00 / A+	4,03 / A+	4,19 / A+	4,09 / A+
	Power supply source				V / Ph / Hz	220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz
	Refrigerant					R32	R32	R32	R32
	Refrigerant charged				g	550	560	850	1300
	Max. discharge pressure				Mpa	4,3	4,3	4,3	4,3
	Max. suction pressure				Mpa	2,5	2,5	2,5	2,5
	Air flow volume				m <sup>3</sup> / h	600	600	900	1300
	Sound power level		Indoor unit (Hi. / Med. / Lo.)		dB (A)	23 / 31 / 36	26 / 31 / 34	30 / 33 / 37	36 / 40 / 44
			Outdoor unit in high mode		dB (A)	61	62	62	66
	Indoor unit weight				Kg	8,5	8,5	10,5	14
	Outdoor unit weight				Kg	18	22,5	28	39
Piping size	Liquid				mm (inch)	1/4	1/4	1/4	1/4
	Gas				mm (inch)	3/8	3/8	1/2	5/8
	Maximum pipe length				m	20	20	25	25
	Maximum pipe height				m	10	10	15	15
	Additional refrigerant charge				g / m	15	15	25	25
	Max chargeless length				m	3	3	3	3
Wiring size	Power supply cord				mm	3 x 1,5	3 x 1,5	3 x 2,5	3 x 2,5
	Indoor & outdoor connection				mm	5 x 1,5	5 x 1,5	5 x 1,5	5 x 1,5
Indoor unit configuration	Dimension	Net dimension (W x D x H)		mm	788 x 198 x 292	788 x 198 x 292	936 x 221 x 316	1121 x 231 x 329	
		Packing dimension (W x D x H)		mm	880 x 290 x 370	880 x 290 x 370	1010 x 310 x 385	1205 x 317 x 400	
Outdoor unit configuration	Compressor model					GSX088BKQA6JT8	KSN98D34UER3	KSN140D53UFZM3	C-6RZ146H3DEF
	Dimension	Net dimension (W x D x H)		mm	650 x 233 x 456	705 x 279 x 530	785 x 300 x 555	900 x 350 x 700	
		Packing dimension (W x D x H)		mm	760 x 315 x 510	825 x 326 x 595	888 x 367 x 590	1020 x 430 x 770	
Operation temperature	Operating range (cooling)				°C	16 - 49	16 - 49	16 - 49	16 - 49
	Operating range (heating)				°C	-15 - 30	-15 - 30	-15 - 30	-15 - 30

The company reserves the right to change the technical characteristics without notice.