



WWW.SENDO.WORLD



HERO X5

NATURAL WARMTH

6KW – 22KW




Wi-Fi Ready



R 290



INVERTER





Integrated circulator



Pressure gauge



Integrated thermostat

HEAT PUMPS

HERO X_S

Wi-Fi R 290 INVERTER



Model		SHP-06HXSP1	SHP-08HXSP1	SHP-12HXSP1	SHP-15HXSP1	SHP-15HXSP3	SHP-22HXSP3	
Heating	Heating Capacity Range	kW	2.5~6.0	3.3 ~ 8.3	4.5 ~ 11.4	5.9 ~ 14.8	5.9 ~ 14.8	8.8 ~ 22.0
	Heating Input Range	kW	0.48~1.44	0.64 ~ 2.18	0.85 ~ 2.95	1.13 ~ 3.83	1.13 ~ 3.83	1.68 ~ 5.77
	COP Range		4.16~5.21	3.81 ~ 5.17	3.81 ~ 5.17	3.86 ~ 5.22	3.86 ~ 5.22	3.81 ~ 5.24
Cooling	Cooling Capacity Range	kW	1.7~4.2	2.4 ~ 5.8	3.3 ~ 8.2	4.3 ~ 10.8	4.3 ~ 10.8	6.2~15.3
	Cooling Input Range	kW	0.53~1.37	0.79 ~ 2.19	1.08 ~ 3.07	1.39 ~ 3.99	1.39 ~ 3.99	1.99~5.60
	EER Range		3.06~3.20	2.65 ~ 3.04	2.67 ~ 3.06	2.71 ~ 3.10	2.71 ~ 3.10	2.73~3.12
	ErP Level (35°C)		A+++	A+++	A+++	A+++	A+++	A+++
DHW	Heating Capacity Range	kW	2.6~5,3	3.7 ~ 7.4	5.2 ~ 10.2	6.6 ~ 13.2	6.6 ~ 13.2	7.8 ~ 17.6
	Heating Input Range	kW	0.56~1.50	0.79 ~ 2.10	1.10 ~ 2.87	1.41 ~ 3.73	1.41 ~ 3.73	7.8 ~ 17.6
	COP Range		3.53~4.64	3.52 ~ 4.69	3.55 ~ 4.71	3.54 ~ 4.67	3.54 ~ 4.67	3.51 ~ 4.66
Power Supply		230V/1Ph/50Hz/60Hz				380V/3Ph/50-60Hz		
Refrigerant		R290						
Net Weight	kg	95	105	115	160	160	166	
Net Dimension (L x W x H) (mm)	mm	1080 x 440 x 761	1080 x 460 x 820	1080 x 460 x 960	1080 x 480 x 1060	1080 x 480 x 1060	1080 x 480 x 1372	
Operating water temperature	°C	20 ~ 75 °C (DWH)						
Operating water temperature	°C	20 ~ 75 °C (max) Heat						
Operating water temperature	°C	7 ~ 35 °C (max) Cooling						

The company reserves the right to change the technical characteristics without notice.